

NN Regression

JSM 2018: Poster 181 - Classroom Demonstration: Deep Learning for Classification and Regression, Int

Eric A. Suess

Department Of Statistics and Biostatistics

CSU East Bay

eric.suess@csueastbay.edu

Example: Compare Simple Linear Regresion to a single layer NN.

The **cars** dataset in R contains two variables stopping *speed* of cars in mph and *dist* in feet. Using speed to predict stopping distance, two models are fit. See the R code.

- a. What function is used to normalize the data?
- b. What percentage of the data is used for *training*? What percentage of the data is used for *testing*?
- c. What is the fitted linear regression model?
- d. What is the correlation between the linear regression predicted values and the values from the test data?
- e. Sketch the NN model that is used to model stopping distance.
- f. What kind of activation function was used in the ANN? Sketch a picture of what the activation function looks like.
- g. What is the correlation between the ANN predicted values and the values from the test data?
- h. Examine the scatterplot of speed by distance with the fitted models. Is the NN fitting a near linear function?
- i. Which model would you use for prediction? Explain.

Answer:

Read in data and examine structure.

```
suppressMessages(library("tidyverse"))

cars <- as.tibble(cars)

## Warning: `as.tibble()` was deprecated in tibble 2.0.0.
## i Please use `as_tibble()` instead.
## i The signature and semantics have changed, see `?as_tibble`.

cars

## # A tibble: 50 x 2
##   speed   dist
##   <dbl> <dbl>
```

```


## 1   4   2
## 2   4   10
## 3   7   4
## 4   7   22
## 5   8   16
## 6   9   10
## 7   10  18
## 8   10  26
## 9   10  34
## 10  11  17
## # ... with 40 more rows

```

```
str(cars)
```

```
## tibble [50 x 2] (S3: tbl_df/tbl/data.frame)
## $ speed: num [1:50] 4 4 7 7 8 9 10 10 10 11 ...
## $ dist : num [1:50] 2 10 4 22 16 10 18 26 34 17 ...
```

```
cars %>% ggplot(aes(x=speed, y=dist)) +  
  geom_point(size = 4) +  
  ggtitle("Cars data")
```



Apply scaling to entire data frame.

```
cars_norm <- cars %>% mutate(speed = scale(speed), dist=scale(dist))
cars_norm
```

```

## # A tibble: 50 x 2
##       speed[,1] dist[,1]
##       <dbl>    <dbl>
## 1     -2.16   -1.59
## 2     -2.16   -1.28
## 3     -1.59   -1.51
## 4     -1.59   -0.814
## 5     -1.40   -1.05
## 6     -1.21   -1.28
## 7     -1.02   -0.969
## 8     -1.02   -0.659
## 9     -1.02   -0.348
## 10    -0.832  -1.01
## # ... with 40 more rows


```

```
str(cars_norm)
```

```
## # tibble [50 x 2] (S3:tbl_df/tbl/data.frame)
## # $ speed: num [1:50, 1] -2.16 -2.16 -1.59 -1.59 -1.4 ...
## # ..- attr(*, "scaled:center")= num 15.4
## # ..- attr(*, "scaled:scale")= num 5.29
## # $ dist : num [1:50, 1] -1.59 -1.28 -1.513 -0.814 -1.047 ...
## # ..- attr(*, "scaled:center")= num 43
## # ..- attr(*, "scaled:scale")= num 25.8
```

```
cars_norm %>% ggplot(aes(x=speed, y=dist)) +  
  geom_point(size = 4) +  
  ggtitle("Scaled cars data") +  
  scale_x_continuous(limits = c(-2.2, 2)) +  
  scale_y_continuous(limits = c(-2, 3))
```

Scaled cars data



Create training and test data.

Side note: This is not done using best practices, the scale() function should only be applied to the training data not the entire dataset. This is a common practice in many machine learning books. This should be corrected.

```
set.seed(12345)

idx <- sample(1:50, 40)

cars_train <- cars_norm[idx, ]
str(cars_train)

## tibble [40 x 2] (S3:tbl_df/tbl/data.frame)
## $ speed: num [1:40, 1] -0.643 -0.4539 -0.0756 0.1135 -0.0756 ...
##   ..- attr(*, "scaled:center")= num 15.4
##   ..- attr(*, "scaled:scale")= num 5.29
## $ dist : num [1:40, 1] -0.737 -0.659 0.428 -0.116 -0.892 ...
##   ..- attr(*, "scaled:center")= num 43
##   ..- attr(*, "scaled:scale")= num 25.8

cars_test <- cars_norm[-idx, ]
str(cars_test)

## tibble [10 x 2] (S3:tbl_df/tbl/data.frame)
## $ speed: num [1:10, 1] -1.399 -1.021 -0.643 -0.454 -0.265 ...
```


```

##   ..- attr(*, "scaled:center")= num 15.4
##   ..- attr(*, "scaled:scale")= num 5.29
## $ dist : num [1:10, 1] -1.047 -0.969 -0.581 -0.348 -0.271 ...
##   ..- attr(*, "scaled:center")= num 43
##   ..- attr(*, "scaled:scale")= num 25.8

cars_train %>% ggplot(aes(x=speed, y=dist)) +
  geom_point(size = 4) +
  ggtitle("Training Data") +
  scale_x_continuous(limits = c(-2.2, 2)) +
  scale_y_continuous(limits = c(-2, 3))

```

Training Data




```

cars_test %>% ggplot(aes(x=speed, y=dist)) +
  geom_point(size = 4) +
  ggtitle("Test Data") +
  scale_x_continuous(limits = c(-2.2, 2)) +
  scale_y_continuous(limits = c(-2, 3))

```

Test Data



Fit a simple linear regression. Train a linear regression model. Predict the Test Data. Compare predicted values with the holdout values.

```
cars_lm <- cars_train %>% lm(dist ~ speed, data = .)

summary(cars_lm)

## 
## Call:
## lm(formula = dist ~ speed, data = .)
## 
## Residuals:
##      Min       1Q   Median       3Q      Max 
## -1.0565 -0.3656 -0.1615  0.3099  1.7617 
## 
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)    
## (Intercept) -0.05570   0.09165  -0.608   0.547    
## speed        0.78873   0.08989   8.774 1.13e-10 ***  
## ---        
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1 
## 
## Residual standard error: 0.5795 on 38 degrees of freedom
## Multiple R-squared:  0.6695, Adjusted R-squared:  0.6608 
## F-statistic: 76.98 on 1 and 38 DF,  p-value: 1.135e-10
```

```

predicted_lm_dist <- predict(cars_lm, cars_test)

# examine the correlation between predicted and actual values
cor(predicted_lm_dist, cars_test$dist)

##          [,1]
## [1,] 0.8055475

```

Fit a NN. Train a neural network model. Compare the R code. It is very similar.

```

library(neuralnet)

## 
## Attaching package: 'neuralnet'

## The following object is masked from 'package:dplyr':
## 
##     compute

set.seed(12345)

cars_model <- cars_train %>% neuralnet(formula = dist ~ speed,
                                             act.fct = "logistic", hidden = 3, linear.output=TRUE)

plot(cars_model)

```


Nice plot with the plotnet() function.

```

library(NeuralNetTools)

par(mar = numeric(4), family = 'serif')
plotnet(cars_model, alpha = 0.6)

```



Predict the Test Data. Compare predicted values with the holdout values.

```
model_results <- compute(cars_model, cars_test[1])

predicted_dist <- model_results$net.result


# examine the correlation between predicted and actual values
cor(predicted_dist, cars_test$dist)

##          [,1]
## [1,] 0.8033258
```

Plot the fitted models.

```
ggplot(data=cars_test, aes(x=speed, y=dist)) +
  geom_point(size = 4) +
  geom_smooth(method='lm', formula=y~x, fill=NA) +
  geom_line(aes(y = predicted_dist)) +
  ggtitle("Test Data Fitted with a Linear Model (blue) and NN (black)") +
  scale_x_continuous(limits = c(-2.2, 2)) +
  scale_y_continuous(limits = c(-2, 3))
```

Test Data Fitted with a Linear Model (blue) and NN (black)



Example: Compare Simple Linear Regression to a Deep Learning, multilayer neural network.


- Do you think this model will overfit?
- What does parsimonious mean?
- Suggest a better measure for goodness-of-fit.

```
cars_model <- cars_train %>% neuralnet(formula = dist ~ speed,
                                         act.fct = "logistic", hidden = c(10,5), linear.output=TRUE)

plot(cars_model)
```

Nice plot with the `plotnet()` function.

```
par(mar = numeric(4), family = 'serif')
plotnet(cars_model, alpha = 0.6)
```



Predict the Test Data. Compare predicted values with the holdout values.

```
model_results <- compute(cars_model, cars_test[1])

predicted_dist <- model_results$net.result

# examine the correlation between predicted and actual values
cor(predicted_dist, cars_test$dist)
```

```
##          [,1]
## [1,] 0.857052
```

Plot the fitted models.

```
ggplot(data=cars_test, aes(x=speed, y=dist)) +
  geom_point(size = 4) +
  geom_smooth(method='lm', formula=y~x, fill=NA) +
  geom_line(aes(y = predicted_dist)) +
  ggtitle("Test Data Fitted with a Linear Model (blue) and NN (black)") +
  scale_x_continuous(limits = c(-2.2, 2)) +
  scale_y_continuous(limits = c(-2, 3))
```

Test Data Fitted with a Linear Model (blue) and NN (black)

